



Fischer GL6K & GL8K Sizes and Configuration Options

Model	Width of Main Deck cm	No. Rotors	No. Blades	HP Requirements	Weight/Kg	Hydraulically adjustable working Width in cm
	Hinged with one or two side sections	Blade Bars	Pivoted Mulching Blades	@ PTO	Without Oil	Expressed with swivel-arm mowers on both sides
GL6K-70-310-430	310	6	12	90 - 120	1450	310-430
GL6K-80-350-490	350	6	12	90 - 120	1530	350-490
GL6K-90-390-530	390	6	12	90 - 120	1630	390-530
GL6K-90-430-590	430	6	12	90 - 120	1700	430-590
GL6K-90-470-630	470	6	12	90 - 120	1750	470-630
GL6K-335-90 SPECIAL	335 +90 one-sided	4	8	90-120	1850	335-415
	This model offers extra off-set and optional input gear-drive positioning. It requires hydraulically engageable rear transport axle for safe tuning. The side-section mower offers unique, hinged terrain adaption of -12° to + 25°. Available with optional hydraulic side-wing lifting facility with float position and transport lock.					
GL8K-70-470-590	470	8	16	90 - 120	1855	470-590
GL8K-80-530-670	530	8	16	120	1950	530-670
GL8K-90-590-750	590	8	16	120	2065	590-750
GL8K-90-650-810	650	8	16	120	2150	650-810
GL8K-90-710-870	710	8	16	120	2220	710-870
Swivel-arm disc sizes	The figure 70 / 80 / 90 refers to the heavy duty swivel-arm disc diameter in cm.					
Note to above model sizes	Model sizes are expressed with swivel-arms on both sides. All models are available with or without swivel-arms, or with one-sided swivel arm mower on request.					