



### Fischer SL2/3 & 4 and Fischer HL sizes and configurations

Model	Working Width cm	No. Rotors	N0. Blades	HP Requirements	Weight/Kg	Side-shift capacity
	All <b>Fischer SL, HL</b> models have recently been reviewed and are now available with the acclaimed, hydraulic, linear side-shift facility available for rear, front and rear&front mounting.					N=neutral, behind centre of the tractor Ex=fully extended side-shift.
<b>SL2/60 125</b>	125-170	2+1	6	40-80	310	N63/63 Ex00/135+60
<b>SL2/60 140</b>	140-190	2+1	6	40-80	330	N70/70 Ex00/145+60
<b>SL2/60 160</b>	160-210	2+1	6	40-80	350	N80/80 Ex00/170+60
<b>SL3/60 180</b>	180-230	3+1	8	40-80	370	N85/95 Ex00/190+60
<b>SL3/60 200</b>	200-250	3+1	8	40-80	390	N85/115 Ex00/210+60
<b>SL3/60 230</b>	230-280	3+1	8	60-80	420	N95/135 Ex00/230+60
<b>SL3/60 250</b>	250-300	3+1	8	60-80	475	N90/110 Ex06/243+60
<b>SL4/60 270</b>	270-340	4+1	10	60-80	500	N135/135Ex45/225+80
<b>SL4/80 310</b>	310-380	4+1	10	60-80	540	N155/155Ex65/245+80
<b>SL4/80 360</b>	360-430	4+1	10	75-100	660	N180/180Ex90/270+80
<b>Extra Equipment</b>	The smaller <b>Fischer SL</b> models come standard with 600mm swivel-arm disc and can be upgraded to the heavy duty 800mm swivel-arm disc. We offer fixed or caster poly-foam filled rubber tires on request. All above options offer optional integrated herbicide equipment and automatic point-spray facility with fine-sensor only.					
	The <b>Fischer HL</b> is like a <b>Fischer SL</b> but <b>without the swivel-arm disc</b> setup. It features 1 centre gear-drive and 4 KEVLAR belt driven blade rotors. Hydraulic, linear Side-Shift and as above, it is available as rear, front and rear&front mountable. We offer various gear-drive speed options.					
<b>HL-270</b>	270	4	8	60-80	380	N135/135Ex45/225
<b>HL-310</b>	310	4	8	60-80	420	N155/155Ex65/245
<b>HL-360</b>	360	4	8	75-100	540	N180/180Ex90/270