


Fischer TWISTER L1 & L2

Model	Hydraulic Side-Shift	+ Manual Side-Shift on request	Total Working Width	Hydraulic oil requirements L/min	Brush Diameters	Brush Spindle Length	Front & Rear Mountable	Recommended Operating Speed	TWISTER Cord with KEVLAR core
	In cm	in cm	in cm	@ 180bar including operating functions	310mm & 450mm	345mm & 550mm	3Point or direct Plate Mounting	@ TWISTER Brush Spindles	Orange: Soft but durable Green: Medium White: Tough, for over-cut and tough conditions
TWISTER L1-S	70	45	75-145	25-30	Yes	Yes	Yes	max.2000rpm	Yes
TWISTER L1-L	70	45	109-179	25-30	Yes	Yes	Yes	max.2000rpm	Yes
TWISTER L2-S	70+70	45/45	150-290	50-60	Yes	Yes	Yes	max.2000rpm	Yes
TWISTER L2-L	70+70	45/45	218-358	50-60	Yes	Yes	Yes	max.2000rpm	Yes
Standard Hydraulic Functions	Transport V position, hydraulic linear side-shift and On/Off.								
Extra Hydraulic Functions	Hydraulic brush head tilt/angle adjustment one side or both sides.								
Other Hydraulics	Oil flow regulator, pressure relief valve, oil filter, non-return valves and hoses with quick couplings.								
Tractor Hydraulic requirements	1x Dedicated constant supply, 1x Dedicated (pressureless) return/dump and 1 x 12V connection for remote control.								
Other Features	Height adjustable metal support wheels, storage stand and diffusion and plant protection guards.								