




Fischer BV2/BV3 Expandable Deck Mower

Model	Working Width cm	No. Rotors	No. Blades	HP Requirements	Weight/Kg
			Pivoted Mulching Blades	PTO Requirements	
BV2 110 - 145	110 - 145	2	4	40-90	415
BV2 125 - 175	125 - 175	2	4	40-90	457
BV2 125-175 special	125 -175	2	4	40-90	424
BV2 125-175 new	125 -175	2	4	40-90	481
BV2 140 - 195	140 - 195	2	4	40-90	468
BV2 140 - 195 new	140 - 195	2	4	40-90	520
BV2 160 - 230	160 - 230	2	4	40-90	595
BV2 170-245 special	170 - 245	2	4	40-90	563
BV2 190 - 260	190 - 260	2	4	60-100	702
BV2 220 - 300	220 - 300	2	4	60-100	818
BV2 250 - 340	250 - 340	2	4	60-100	915
BV3 180 - 260	180 - 260	3	6	60-100	680
BV3 195 - 290	195 - 290	3	6	85-110	702
BV3 250-360	250 - 360	3	6	85-110	936
special	Lighter construction using thinner higher quality metal sheeting.				
new	Front wheels are mid frame mounted - not mowing side-ways when shifted.				
	The Fischer BV2 is available with hydraulic rail fine-sensor technology offering automatic, linear row width adjustment. For further details, please contact us.				