Description	Order Code	AUD Unit prices bought together with frame	Description
Fischer Flex1			One-sided MultiTool frame (front right). Excluding tool, measured from the centre of the 3Point linkage: 440mm to 1,135mm or 940 to 1,635 with Flex-04 arm extensions.
Fischer Flex2-XS			Extra Small, double-sided MultiTool frame. Excluding tool, measured from the centre of the 3Point linkage: 360mm each side, or total width excluding tool @ 720mm to 1,280mm or 2,280mm with Flex-04 arm extensions.
Fischer Flex2-S			Small, double-sided MultiTool frame. Excluding tool, measured from the centre of the 3Point linkage: 435mm each side, or total width excluding tool @ 870mm to 1,748mm or 2,748mm with Flex-04 arm extensions.
Fischer Flex2-L			Large, double-sided MultiTool frame. Excluding tool, measured from the centre of the 3Point linkage: 561mm each side, or total width excluding tool @ 1,122mm to 2,522mm or 3,522mm with Flex-04 arm extensions.
Height adjustable centre support wheels.	Flex-01	On request	Centre front support wheel with 2 x height adjustable solid rubber wheels.

Fischer Flex1 and Flex2-XS, Flex2-S & Flex2-L Weeding System (updated 24/04/2020)

Description		Order Code	AUD Unit prices bought together with frame	Description
Front plate mountable lifting facility (replacing front 3Point linkage)		Flex-33	On request	The Flex-33 is an alternative to retrofitting a front linkage to a tractor at approx. 1/2 of the price. It offers hydraulic up/down and can be front plate mounted and offers universal 3Point attachment.
Individual implement lifting blocks for RH re uneven row ends		Flex-31	On request	The Flex-31 can be mounted to both sides and allows to lift the tool bracket out off the ground in cases of uneven
Individual implement angle adjustment for RH and FH		Flex-32	On request	The Flex-32 can be mounted to both sides and allows to hydraulically adjust the working angle.
Individual implement angle adjustment FH only	-1	Flex-30	On request	The Flex-30 can be mounted to both sides and allows to hydraulically adjust the working angle of the FH only.
Simple arm extension + 500mm		Extension	On request	Simple arm extension + 500mm
Extra narrow attachment bracket	No.	Narrow mount	On request	To be specified at time of order.
Grader-shield left & right / price each.		Grader-shield	On request	Self levelling grader-blade.
Post-lift with nitrogen tank (500mm)	A Construction of the second s	Post-lift	On request	Post-lift attachment for one-way hydraulic with attachment bracket (500mm) for centre mounting.

Description		Order Code	AUD Unit prices bought together with frame	Description
Working width extension (+500mm) and hydraulic implement angle adjustment and transport positioning, left or right / each.		Flex-04	On request	The Flex-04 is a Flex frame extension (+500mm) with additional, inbuilt hydraulic working angle adjustment - it is necessary for mounded rows and lift-up for travel and storage.
Hydraulic cylinder for implement tilt/ angle adjustment (TWISTER, HDT etc.) one side	~	Flex-10	On request	Hydraulic cylinder for implement tilt/ angle adjustment on TWISTER, HDT-400 & 600 and FKT-420 (one side).
Hydraulic cylinder for implement tilt/ angle adjustment (TWISTER, HDT etc.) both sides	*	Flex-09	On request	Hydraulic cylinders for implement tilt/ angle adjustment on TWISTER, HDT-400 & 600 and FKT-420 (both sides).
Side crimping rollers for Flex 1 & 2 (length 800mm) left or right		Flex-02	On request	Centre weed crimping roller (folds, and crips weeds, and pushes the stem of the weeds into the ground. Used in biodynamic growing to crimp cover- crops instead of mowing.
Centre crimping roller for Flex2 (length 1200mm) with manual adjustment.		Flex-03	On request	Centre weed crimping roller (folds, and crips weeds, and pushes the stem of the weeds into the ground. Used in biodynamic growing to crimp cover- crops instead of mowing.
Centre crimping roller for Flex2 (length 1200mm) with hydraulic fold up function.		Flex	On request	Centre weed crimping roller (folds, and crips weeds, and pushes the stem of the weeds into the ground. Used in biodynamic growing to crimp cover- crops instead of mowing.

Description		Order Code	AUD Unit prices bought together with frame	Description
Centre crimping roller for Flex2 (length 1600mm) with manual adjustment.		Flex	On request	Centre weed crimping roller (folds, and crips weeds, and pushes the stem of the weeds into the ground. Used in biodynamic growing to crimp cover- crops instead of mowing.
Centre crimping roller for Flex2 (length 1600mm) with hydraulic fold up function.		Flex	On request	Centre weed crimping roller (folds, and crips weeds, and pushes the stem of the weeds into the ground. Used in biodynamic growing to crimp cover- crops instead of mowing.
Implements:				
		RH2-S	On request	Patented Roller Hoe with 2 star rollers and diffusion guards.
Roller Hoe (patented)	- Ann	RH3-S	On request	Patented Roller Hoe with 3 star rollers and diffusion guards.
Roller Hoe (patented)	A DATE SA	RH-4SRN	On request	Patented Roller Hoe with 4 star rollers and diffusion guards.
Roller Hoe (patented)		RH-5SRN	On request	Patented Roller Hoe with 5 star rollers and diffusion guards.

Description		Order Code	AUD Unit prices bought together with frame	Description
Roller Hoe (patented)	A LEAST	RH-6SRN	On request	Patented Roller Hoe with 6 star rollers and diffusion guards.
Roller Hoe (patented)	THE THE SECOND	RH-7SRN	On request	Patented Roller Hoe with 7 star rollers and diffusion guards.
Dual Roller Hoe (patented) NEW	A.A.	RH4 new	On request	Dual Roller hoe - expandable with larger segments on request - requires attachment kit.
Dual Roller Hoe (patented) New	- Aller	RH5 right/left new	On request	Dual Roller hoe - expandable with larger segments on request - requires attachment kit.
Dual Roller Hoe (patented) New	ANT	RH6 right/left new	On request	Dual Roller hoe - expandable with larger segments on request - requires attachment kit.
Disc Plow		TP-1	On request	Single disc-plow for undervine mounding.

Description		Order Code	AUD Unit prices bought together with frame	Description
Double Disc Plow	0)	TP-2	On request	Double disc-plow for undervine mounding.
Finger Weeder Yellow		FH-54 Yellow	On request	D54cm flex rubber fingers weeder pushes loos soil in-between the vines and rips loos roots of weeds to the side. Yellow = thinner for lighter soils.
Finger Weeder Yellow		FH-70 Yellow	On request	D70cm flex rubber fingers weeder pushes loos soil in-between the vines and rips loos roots of weeds to the side. Yellow = thinner for lighter soils.
Finger Weeder Orange		FH-100	On request	D100cm large rubber fingers weeder pushes loos soil in-between the vines and rips loos roots of weeds to the side. Orange = medium strength.
Finger Weeder Yellow		FH-54 Red	On request	D54cm hard rubber fingers weeder pushes loos soil in-between the vines and rips loos roots of weeds to the side. Red = tough & very durable
Finger Weeder Yellow		FH-70 Red	On request	D70cm hard rubber fingers weeder pushes loos soil in-between the vines and rips loos roots of weeds to the side. Red = tough & very durable
Bio-Brush Weeder D300 or D450		TWISTER 1	On request	High speed bio-brush weeder D300 or D4500, L550 with plant guard, hydraulic motor and gas shock absorber.

Description		Order Code	AUD Unit prices bought together with frame	Description
Bio-Cord Weeder NEW		TORNADO	On request	New Fischer Bio-Cord Weeder for undervine and tree-line weeding and de-suckering.
Mower Disc with Hydraulic Fine- Sensor and Support Wheel		HDT-400	On request	D400mm disc mower with lighter blades for fine-cut with gliding disc, inclusive hydraulic motor and hydraulic fine-sensor technology.
Mower Disc with Hydraulic Fine- Sensor and Support Wheel		HDT-600	On request	D600mm disc mower with heavy-duty blades and armour steel gliding disc, inclusive hydraulic motor and hydraulic fine-sensor technology.
Mower Disc with Hydraulic Fine- Sensor and Support Wheel		HDT-800	On request	D800mm disc mower with heavy-duty blades and armour steel gliding disc, inclusive hydraulic motor and hydraulic fine-sensor technology.
Cultivator Head with Hydraulic Fine- sensor Technology and Support Wheel		FKT-420	On request	Heavy duty D420mm bumbler head for undervine cultivating. Includes hydraulic motor and fine-sensor technology.
Cane Sweeper D800	- Alexandre	RSO	On request	Sweeper head with Nylon rods, includes hydraulic motor and mounting bracket. Requires oil flow regulator - double sided unit requires hydraulic oil splitter and/or e/h block for 2 x motors + remote control.
Single sided Dodge-Blade with hydraulic fine-sensor, operating components and remote control		UTR-60	On request	500mm undervine dodge blade with hydraulic fine-sensor technology including operating components (also for combo RH3-S/UTR).

Description		Order Code	AUD Unit prices bought together with frame	Description
Double sided Dodge-Blade with hydraulic fine-sensor, operating components and remote control		UTR-60	On request	500mm undervine dodge blade with hydraulic fine-sensor technology including operating components (also for combo RH3-S/UTR).
Double line-guiding support wheels with attachment bracket		UTR	On request	Track-guide wheels, can be exchanged with RH or TP-1.
Hydraulic components:				
Hydraulic Rail Fine-Sensor Technology both sides only.		Automatic Row Width Adjustment for RH + FH Weeders	On request	Integrated width adjustable hydraulic fine-sensor technology inclusive operating components and in-cabin remote control - controls individual sides.
Hydraulic function upgrade with in- cabin remote control (12V)		Upgrade to Hydraulic Fine- sensor	On request	Hydraulic upgrade, allowing to regulate the reaction speed of the return of the rail sensors in case of large gaps in plant line.
Frame mounted hydraulic self- supply (PTO) for one side 40Lt.	*	Flex-06	On request	Exclusive for TWISTER, tank 40Lt. pump etc. One side only!
Frame mounted hydraulic self- supply (PTO) for both sides 40Lt.	*te	Flex-05	On request	Exclusive for TWISTER, Tank 40Lt. pump etc. For both sides.
Frame integrated hydraulic self- supply (PTO) for one side 100Lt.	₩.	Flex-29	On request	For HDT400/600, FKT-420 + TWISTER tank 100Lt. pump etc. One side only!

Description		Order Code	AUD Unit prices bought together with frame	Description
Frame integrated hydraulic self- supply (PTO) for both side	The second se	Flex-28	On request	For HDT400/600, FKT-420 + TWISTER tank, gear-drive for PTO 100Lt. pump etc. For both sides.
Stand alone, 3Point setup for above hydraulic self-supply systems to combine with Flex-06/Flex-05/ Flex-29/Flex-28		Power-Pack	On request	Stand alone 3Point for above hydraulic sea-supply systems.
Stand alone, 3Point setup with continuous PTP port and rear 3Point for above hydraulic self-supply systems to combine with Flex-06/ Flex-05/Flex-29/Flex-28		Power-Pack	On request	Stand alone 3Point for above hydraulic self supply systems with continuous PTO port and rear 3Point to fit mower or spray unit.
Oil Splitter for synchronised side- shift		Flex-14	On request	Hydraulic oil splitter for synchronised linear side-shift and splitting oil supply for hydraulic implement heads.
Seperate oil-flow regulator	۵	Flex-27	On request	Hydraulic oil flow regulator.
E/H Control Block for 1 Motor (On/ Off) with oil flow regulator, pressure relief valve and cary over for frame functions (TWISTER/TORNADO).		Flex-15	On request	Required for Fischer TWISTER 1 and RSO 1 Cane Sweeper, if e/h control is required - on/off + frame functions.
E/H Control Block for 1 Motor (On/ Off) with oil flow regulator, pressure relief valve including fine-sensor supply one side (HDT/FKT).		Flex-18	On request	Required for one-sided HDT-400 & 600 and FKT-420 which feature hydraulic fine-sensor technology
E/H Control Block for 2 Motor (On/ Off) with oil flow regulator, pressure relief valve and cary over for frame functions		Flex-16	On request	Required for all configurations with 2 motors, frame functions and requires Flex-19 for fine-sensor technology for HDT-400 & 600 and FKT-420.

Description		Order Code	AUD Unit prices bought together with frame	Description
E/H Control Block for 2 Motor (On/ Off) with oil flow regulator, pressure relief valve - NO carry over		Flex-17	On request	Required 2 motors but NO frame functions and requires Flex-19 for fine- sensor technology for HDT-400 & 600 and FKT-420.
E/H Control Block for hydraulic fine- sensor technology both sides, including oil flow regulator, flow splitter and pressure relief valve.		Flex-19	On request	Only required to run fine-sensor technology for HDT-400 & 600 and FKT-420.
Integrated oil cooler (12V) with automatic cleaning cycle.		Small	On request	In-line oil cooler for TWISTER and TORNADO.
Integrated oil cooler (12V) with automatic cleaning cycle.		Large	On request	In-line oil cooler for HDT-400 / HDT-600 / HDT-800 / and FKT-420
Electronic for self-cleaning cycle		Both sizes	On request	Electronic for self-cleaning cycle
Hydraulic changeover valve 4-way, including hydraulic hoses and fittings.	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	Assesory	On request	Hydraulic change-over valve to operate 2 functions with 1 hydraulic remote.
Hydraulic changeover valve 6-way, including hydraulic hoses and fittings.	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	Assesory	On request	Hydraulic change-over valve to operate 3 functions with 1 hydraulic remote.
Hydraulic control valve (double acting) for 2 functions.		Assesory	On request	Electrohydraulic control valve (12V) double acting, for 2 functions, <u>requires</u> <u>remote control.</u> (requ. reduced pressure, constant oil supply & return).

Description		Order Code	AUD Unit prices bought together with frame	Description	
Hydraulic control valve (double acting) for 3 functions.		Assesory	On request	Electrohydraulic control valve (12V) double acting, for 3 functions, <u>requires</u> <u>remote control.</u> (requ. reduced pressure, constant oil supply & return).	
Hydraulic control valve (double acting) for 4 functions.		Assesory	On request	Electrohydraulic control valve (12V) double acting, for 4 functions, <u>requires</u> <u>remote control.</u> (requ. reduced pressure, constant oil supply & return).	
Hydraulic control valve (double acting) for 6 functions.		Assesory	On request	Electrohydraulic control valve (12V) double acting, for 6 functions, <u>requires</u> <u>remote control.</u> (requ. reduced pressure, constant oil supply & return).	
Remote Control one side		Remote	On request	Remote control unit for one side includes On/Off and isolating plug for leaving remote in tractor after use.	
Remote Control both sides		Remote	On request	Remote control unit for both sides includes On/Off and isolating plug for leaving remote in tractor after use.	
Remote control unit with Joystick for all functions	66	Joystick	On request	Remote control with Joystick to control all functions (12V).	
Hydraulic operating components	Please contact us to discuss the various hydraulic oil requirements and necessary operating components for individual frame/implement configurations and tractor capacities.				
Hydraulic self-supply units	We offer various 3Point mountable, frame integrated and mower mounted hydraulic self-supply units you can see some of them on our website under Additional Equipment <u>www.fischeraustralis.com.au</u> or give me a call to discuss: +61 (0)8 94333 555 / 0409 572 581.				